

Low Capacitance RS-485 Computer Cables 0.34MM² Overall Screen, HFFR/LSZH Sheath




C5609, C5610, C5611, C5612

Applications

Building Management Systems (BMS), Access Control, Instrumentation

Cross Section Drawing



Design

Unit	Properties
Conductor	Tinned Copper wire, flexible
Insulation	Foam PE Pair 1: WHITE/Blue + BLUE/White Pair 2: WHITE/Orange + ORANGE/White Pair 3: WHITE/Green + GREEN/White Pair 4: WHITE/Brown + BROWN/White
Cabling	N Pairs twisted together
Screen	Aluminium/Polyester 115% Coverage
Drain Wire	Tinned Copper wire
Braid	Tinned Copper wire
Sheath Material	Halogen Free Flame Retardant (HFFR/LSZH) Standard colour: Purple
Standard Put Up Length	305 or 500 meters

*Other Colors, Put Up Lengths and structures can be manufactured upon request, please contact your local B3 International sales representative.

Low Capacitance RS-485 Computer Cables

0.34MM² Overall Screen, HFFR/LSZH Sheath



C5609, C5610, C5611, C5612

Physical Characteristics

Part Number	C5609	C5610	C5611	C5612
Number of pairs	1	2	3	4
Cross Section (mm ²)	0.34			
Nom. Radial Thickness Insulation (mm)	0.6			
Drain Wire Size (AWG)	24(7 x 32)			
Coverage braid (%)	65			
Nom. Radial Thickness Sheath (mm)	0.8			
Nom. Overall Diameter (mm)	6.1	8.0	9.3	10.3
Operating Temperature (°C)	-25 / +75			
Max. Pulling Tension (N)	265	355	400	445
Min. Bend Radius (install) (mm)	60	80	95	105
Nominal Cable Weight (kg/km)	46.7	76.7	97	119.1

Electrical Characteristics

Part Number	C5609	C5610	C5611	C5612
No of pairs	1	2	3	4
Max. DC Resistance Conductor (Ω/km)	57.4			
Max. DC Resistance Screen (Ω/km)	20			
Nominal Impedance (Ω)	120			
Capacitance core to core (pF/m)	34	35	38	38
Capacitance core to rest (pF/m)	65	66	69	69
Nom. Attenuation at 1 MHz (dB/100m)	2.05			
Max. Recom. Current @ 25°C (Amps)	2.7			
Max. Operating Voltage (Vrms)	300			

Reference Standards

(BS)EN 50290-2
IEC 60228
IEC 60332-1
IEC 61034, IEC 60754-1 & -2
RoHS directives