

Category 6 Data Cables

23AWG. SFTP, SWA Armoured with PVC or LSZH-HFFR Sheath




C4927, C5893

Applications

Twisted pair cable suitable for Local Area Networks and Video Applications delivering 1000base-t Gigabit Ethernet, 100BASE-TX Fast Ethernet, 622 Mbps ATM, 155 Mbps ATM and Composite Video.

Cross Section Drawing



Design

Unit	Properties
Conductor	Solid Plain Copper Wire
Insulation	Solid Polyethylene Pair 1: WHITE/Blue + BLUE Pair 2: WHITE/Orange + ORANGE Pair 3: WHITE/Green + GREEN Pair 4: WHITE/Brown + BROWN
Pair	Two wires twisted together
Filler	Cross support
Screen	Aluminium/Polyester tape
Drain Wire	Tinned Copper wire
Braiding	Tinned Copper wire
Bedding	Polyvinyl Chloride (PVC) or Halogen Free Flame Retardant (HFFR)
Armouring	Galvanized Steel Wire
Sheath Material	UV-Resistant Polyvinyl Chloride (PVC) or Halogen Free Flame Retardant (HFFR) Standard Color: Black
Standard Put Up Length	305 metres

*Other Colors, Put Up Lengths and structures can be manufactured upon request, please contact your local B3 International sales representative.

Category 6 Data Cables

23AWG. SFTP, SWA Armoured with PVC or LSZH-HFFR Sheath



C4927, C5893

Physical Characteristics

Part Number	C4927	C5893
Sheath Type	PVC	HFFR
Screen Type	SFTP	
No. of Pairs	4	
Conductor Size (AMG)	23	
Drain Wire Size (AMG)	24	
Screen Coverage (%)	115	
Braiding Coverage (%)	45	
Nom. Radial Thickness Bedding (mm)	0.80	
Nom. Bedding Diameter (mm)	8.60	
Nom. Steel Wire Diameter (mm)	0.90	
Nom. Radial Thickness Sheath (mm)	0.90	
Nom. Overall Diameter (mm)	12.5	
Operating Temperature (°C)	-20°C to +60°C	
Min. Bend Radius (install) (mm)	125	

Electrical Characteristics at 20°C

Conductor Resistance (Ohm/100m)	Mutual Capacitance at 1KHz (pF/m)	Input Impedance (Ohm)	Velocity of Propagation (%)	Maximum Delay Skew (ns/100m)	Max. Operating Voltage (Volts RMS)
9.38	56	100 ± 15	67	45	300

Frequency (MHz)	Return Loss (dB/100m)	Maximum Attenuation (dB/100m)	Minimum NEXT (dB)	Maximum Time Delay (ns/100m)	Minimum PSNEXT (dB)	Minimum ELFEXT (dB)	Minimum PSELFEXT (dB)
1	20.0	2.0	74.3	570.00	72.3	67.8	64.8
4	23.0	3.8	65.3	552.00	63.3	55.8	52.8
8	24.5	5.3	60.8	546.73	58.8	49.7	46.7
10	25.0	6.0	59.3	545.38	57.3	47.8	44.8
16	25.0	7.6	56.2	543.00	54.2	43.7	40.7
20	25.0	8.5	54.8	542.05	52.8	41.8	38.8
25	24.3	9.5	53.3	541.20	51.3	39.8	36.8
31.25	23.6	10.7	51.9	540.44	49.9	37.9	34.9
62.5	21.5	15.4	47.4	538.55	45.4	31.9	28.9
100	20.1	19.8	44.3	537.80	42.3	27.8	24.8
200	18.0	29.0	39.8	536.54	37.8	21.8	18.8
250	17.3	32.8	38.3	536.27	36.3	19.8	16.8

Reference Standards

EN 50290-2	ANSI/TIA/EIA-568-C2
ISO 11801	IEC 60228
IEC 61156-5	RoHS directives
IEC 61034 (only HFFR)	IEC 60754-1&-2 (only HFFR)
IEC 60332-3-24 (only HFFR)	