

Audio Control & Instrumentation Cable 2C to 4C, 22AWG, Unscreened,

PVC Sheath



C4598, C4599, C4600

Applications

Multi-Conductor cables suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

Cross Section Drawing



Design

Unit	Properties
Conductor	Flexible Tinned Copper wire
Insulation	Polypropylene Core 1: Black Core 2: Red Core 3: Green Core 4: White
Sheath Material	Flame-Retardant Polyvinyl Chloride (PVC) Standard colour: Grey
Standard Put Up Length	305 meters

*Other Colors, Put Up Lengths and structures can be manufactured upon request, please contact your local B3 International sales representative.

Audio Control & Instrumentation Cable 2C to 4C, 22AWG, Unscreened,

PVC Sheath



C4598, C4599, C4600

Physical Characteristics

Part Number	C4598	C4599	C4600
No of cores	2	3	4
Conductor Configuration (mm)	22AWG (7 x 30)		
Nom. Radial Thickness Insulation (mm)	0.28	0.28	0.28
Nom. Radial Thickness Sheath(mm)	0.40	0.40	0.81
Nom. Overall Diameter (mm)	3.4	3.6	4.0
Operating Temperature (°C)	-25 / +75		
Max. Recommended Pulling Tension (N)	80	120	155
Min. Bend Radius (install) (mm)	34	36	40
Nominal Cable Weight (kg/km)	16.8	22.3	29.4

Electrical Characteristics

Part Number	C4598	C4599	C4600
No of cores x 22AWG (7 x 30)	2	3	4
Nom. DC Resistance Conductor (Ω /km)	51.2		
Capacitance conductor to conductor (Pf/m)	41	49	49
Nominal Inductance (μ H/m)	0.66	0.56	0.56
Max. Recom. Current @ 25°C (Amps)	2.9	2.9	2.4
Max. Operating Voltage (Vrms)	300		

Reference Standards

(BS) EN 50290-2
IEC 60228
IEC 60332-1
RoHS directives