

# Category 6 Data Cable

## 23AWG. UTP or FTP with Plenum Rated PVC Sheath



C8037, C8038

### Applications

Twisted pair cable suitable for Local Area Networks and Video Applications delivering 1000base-t Gigabit Ethernet, 100BASE-TX Fast Ethernet, 622 Mbps ATM, 155 Mbps ATM and Composite Video.

### Cross Section Drawing



### Design

Unit	Properties
Conductor	Solid Plain Copper Wire
Insulation	FEP Pair 1: WHITE/BLUE Pair 2: WHITE/ORANGE Pair 3: WHITE/GREEN Pair 4: WHITE/BROWN
Pair	Two wires twisted together
Filler	Cross support
Drain Wire (FTP only)	Tinned Copper wire
Screen(FTP only)	Aluminium/Polyester tape
Rip Cord	Nylon Yarn
Sheath Material	Polyvinyl Chloride (PVC) Standard Color: Grey
Standard Put Up Length	305 metres

\*Other Colors, Put Up Lengths and structures can be manufactured upon request, please contact your local B3 International sales representative.

# Category 6 Data Cable

## 23AWG. UTP or FTP with Plenum Rated PVC Sheath



C8037, C8038

### Physical Characteristics

Part Number	C8037	C8038
Sheath Material	CMP PVC	CMP PVC
Screen type	UTP	FTP
No. of Pairs	4	
Conductor Size (AMG)	23	
Drain Wire Size (AMG)	-	26
Screen Coverage (%)	-	115
Nom. Radial Thickness Sheath (mm)	0.43	
Nom. Overall Diameter (mm)	5.6	7.2
Operating Temperature (°C)	-20°C to +60°C	
Min. Bend Radius (install) (mm)	56	72
Nominal Cable Weight (kg/km)	40.5	56
Maximum Pulling Tension (Newton)	160	200

### Electrical Characteristics at 20°C

Conductor Resistance (Ohm/100m)	Mutual Capacitance (pF/m)		Input Impedance (Ohm)	Velocity of Propagation (%)	Maximum Delay Skew (ns/100m)	Max. Operating Voltage (Volts RMS)
	UTP	FTP				
9.38	47	48	100 ± 15	67	45	300

Frequency (MHz)	Return Loss (dB/100m)	Maximum Attenuation (dB/100m)	Minimum NEXT (dB)	Maximum Time Delay (ns/100m)	Minimum PSNEXT (dB)	Minimum ELFEXT (dB)	Minimum PSELFEXT (dB)
1	20.0	2.0	74.3	570.00	72.3	67.8	64.8
4	23.0	3.8	65.3	552.00	63.3	55.8	52.8
8	24.5	5.3	60.8	546.73	58.8	49.7	46.7
10	25.0	6.0	59.3	545.38	57.3	47.8	44.8
16	25.0	7.6	56.2	543.00	54.2	43.7	40.7
20	25.0	8.5	54.8	542.05	52.8	41.8	38.8
25	24.3	9.5	53.3	541.20	51.3	39.8	36.8
31.25	23.6	10.7	51.9	540.44	49.9	37.9	34.9
62.5	21.5	15.4	47.4	538.55	45.4	31.9	28.9
100	20.1	19.8	44.3	537.80	42.3	27.8	24.8
200	18.0	29.0	39.8	536.54	37.8	21.8	18.8
250	17.3	32.8	38.3	536.27	36.3	19.8	16.8

# Category 6 Data Cable

23AWG. UTP or FTP with Plenum Rated PVC Sheath



---

C8037, C8038

## Reference Standards

EN 50290-2
ISO 11801
ANSI/TIA/EIA-568-C2
UL 910 CMP
RoHS directives